



Windows Hello compatible webcam with built-in privacy lens cover



JPL Vision Access

Universal 1080p HD 30fps webcam

Ideal for use where office security is essential

Ease of access to your device with Windows Hello facial recognition

Plug & play solution - No software or downloads needed

96° Field of view

Dual stereo full duplexed microphones for smooth natural conversations

Built-in privacy lens cover

Built-in camera in-use LED indicator

USB Type-A and USB Type-C connectivity included

Multi-angled desk mount / monitor mount (as well as tripod fixing screw option on the base) giving full 360° camera rotation and 90° camera forward tilt

2 year standard repair or replacement warranty



Optional mounting suggestion. Tripod not included




JPL Vision Access

Windows Hello compatible USB webcam with a full HD 1080p glass lens, built-in privacy lens cover, USB-A and USB-C connectivity to allow optional connection to any USB-A or USB-C device.

Compatible with all major softphones.

Plug & play solution - No additional software or downloads needed.



Overview

Features	HD 1920 x 1080p Camera Full HD 1080p glass lens - No optical distortion Built-in privacy lens cover Two full duplexed microphones - Built in dual stereo Built-in camera in-use LED indicator USB 2.0 Type-A and USB-C connectivity Desk mount, monitor mount and universal thread for tripod option Full 360° camera rotation including 90° tilt for over desk viewing Automatic low-light correction AEC – Automatic Echo Cancellation ANS – Automatic Noise Suppression
Certifications	UKCA, CE, FCC, RoHS, REACH
Unit Dimensions	92,5 x 52 x 31 mm
Warranty	24 Month repair or replacement warranty
MOQ	Master Shipping Carton: 40
SKU:	575-400-001
EAN:	5060126959786

Technical Data

Camera parameters:	
IR Camera SENSOR:	Sensor Type 1/9" CMOS Array Size 1280*720 30FPS Pixel Size 1.4 μm x 1.4 μm / BSI
RGB Camera SENSOR:	Sensor Type 1/2.9" CMOS Array Size 1920*1080P 30FPS Pixel Size 2.8 μm*2.8 μm FSI
IR Lens:	Construction 3P IR Filter 850nm FOV D=85±% F/No 2.4±5% TV Distortion <-2.6%
RGB Lens:	Construction 1G4P+R IR Filter 850nm FOV D=96±% F/No 2.5±5% TV Distortion <-0.9%
MIC:	Dimensional Ø4.0*1.5mm Sensitivity -38±3db S/N ratio 60db Pick-up distance 3m
Temperature(Operation)	-10°C to 60°C
Temperature(Storage)	-10°C to 60°C
USB Power Supply Voltage	DC 5V
Interface	USB 2.0 USB-A/TYPE-C
Operating System Request	Windows 10-11 (Windows Hello)
AGE/AEC/White Balance	Auto
Supports compression formats	MJPEG/YUV