SPECS & DETAILS LOGITECH H650E

DIMENSIONS

- Height x Width x Depth: 6.5 in (165 mm) x 6.8 in (174 mm) x 2.0 in (50 mm)
- Weight: 4.2 oz (120 g) (Stereo)
- Weight: 3.3 oz (93 g) (Mono)

SYSTEM REQUIREMENTS

COMPATIBLE WITH

Windows Vista®, Windows® 7 or Windows 8 (32-bit or 64-bit), Windows 10
Mac® OS X® 10.7 or higher

Linux®

Available USB port

DRIVERS/SOFTWARE DOWNLOADS

Recommended: Plug-ins for Jabber[™] and Skype
Availability: Select the H650e product at www.lexair.com.

- APPLICATION COMPATIBILITY
- Compatible with most leading UC platforms such as Skype[™] and Skype for Business, Google Hangouts Pro, Cisco[®], and more

CERTIFICATIONS

Certified for Skype for Business; Cisco® compatible*

TECHNICAL SPECIFICATIONS

MICROPHONE (TX)

o Type: Bi-directional ECM

Frequency response: 100 Hz - 10 KHZ

Sensitivity: Type: -45 dB +/- 3 dB

Distortion: <10% @ 1kHz, 15dBPa (MRP) input

Operating voltage: 1.4 - 5.0V DC

SPEAKERS (RX)

^{*}See <u>Cisco Compatibility Matrix</u> for the latest version.

Frequency response: 50 Hz - 10 kHz (Diffuse field)
Sensitivity: 90dB ±3 dB at 1KHz, Input 0.56V/10 mm free field

Distortion: < 4% @ 1kHz, 0dBm0, 1kHz

ATTRIBUTE

o In-call LED red-light indicator

PACKAGE CONTENTS

Headphone with in-line control Quick Start guide and warranty information Carrying bag

WARRANTY INFORMATION

2-Year Limited Hardware Warranty

PART NUMBER

STEREO

PN 981-000518

MONO

PN 981-000513