DIMENSIONS

HEADSET:

- Height x Width x Depth: 6.5 in (165 mm) x 6.8 in (174 mm) x 2.0 in (50 mm)
- Weight: 4.5 oz (128 g) (Dual)
- Weight: 3.1 oz (88 g) (Mono)

BASE:

- Height x Width x Depth: 5 in (128 mm) x 2.8 in (73 mm) x 3.3 in (82 mm)
- Weight: 1.8 lb (475 g)

SYSTEM REQUIREMENTS

COMPATIBLE WITH

WindowsVista®, Windows® 7 or Windows 8 (32-bit or 64-bit), Windows 10
 Mac® OS X® 10.7 or higher

Linux®

Available USB port

AC power

DRIVERS/SOFTWARE DOWNLOADS

Recommended: Plug-ins for Jabber™ and Skype™
 Availability: Select the H820e product on www.lexair.com

APPLICATION COMPATIBILITY

- Compatible with most leading UC platforms such as Skype and Skype for Business,
 Google Hangouts Pro, Cisco¹, and more.
 - ¹ See <u>Cisco Compatibility Matrix</u> for the latest version.

CERTIFICATIONS

- Certified for Skype for Business; Cisco® compatible.¹
 - ¹ See <u>Cisco Compatibility Matrix</u> for the latest version.

OTHER ATTRIBUTES

In-call LED red light indicator on backside of boom
 Mute LED red-light indicator on boom

TECHNICAL SPECIFICATIONS

MICROPHONE (TX)

0

- Type: Bi-directional ECM
- Frequency response: 100 Hz 7 KHZ
- Sensitivity: -45 dB +/- 3 dB
- Distortion: <10% @ 1kHz, 10dBPa (MRP) input
- Operating voltage: 1.4 5.0V DC

SPEAKERS (RX)

0

- Frequency response: 150 Hz 7kHz (ITU-T TIA920)
- Sensitivity: 103dB ±3 dB at 1KHz, Input 1mW/ Type 4153 artificial ear
- Distortion: < 4% @ 1kHz, 0dBm0, 1kHz

BATTERY

0

- Type: Lithium ion
- Weight: 9 g
- Capacity: 430mAh

PACKAGE CONTENTS

Headset Charging stand
AC power adapter
USB cable
Quick Start guide and warranty card

Quick Start guide and warranty card

WARRANTY INFORMATION

2-Year Limited Hardware Warranty

PART NUMBER

STEREO

PN 981-000516

MONO

PN 981-000511