

POLY ROVE R8 DECT™ REPEATER



SPECIFICATIONS

DECT™ FREQUENCY

- 1920-1930 MHz (North America SKU)
- 1880-1900 MHz (EU/ANZ/UK SKU)

RANGE

- Indoor: up to 165 ft (50 m)
- Outdoor: up to 980 ft (300 m)
- Range increases by up to 50 m or up to 300 m depending on environment as a base station or repeater is added

GENERAL FEATURES

- Extends DECT™ coverage
- Supports automatic handover of calls
- Up to 2 simultaneous calls per repeater
- Up to 6 repeaters per base station
- Up to 3 repeaters in cascade mode
- Automatic Handover of Calls between Cells
- Air synchronization
- Encrypted Daisy Chained
- Auto Configuration on Single and Dual Cell
- Zero Touch Installation
- 12 Slot Support
- DECT™ Security Step B
- LED Indicator

PHYSICAL FEATURES

- External Universal AC adapter (5V 2A DC)
- Wall Mountable

POLY ROVE R8 DECT™ REPEATER COMES WITH:

- Repeater
- Stand
- Power Adapter
- Wall Mounting Kit
- Quick Start Card
- Safety Sheet²

COMPLIANCE

- USA FCC
- Canada IC RSS
- EEA CE
- AU/NZ RCM
- NZ Telepermit
- Hong Kong HKCA
- Singapore IMDA TS CT-CTS
- ROHS compliant
- ENERGY STAR

SAFETY

- UL 62368-1
- CE Mark
- CAN/CSA C22.2 No 62368-1
- EN 60950-1 and 62368-1
- IEC 60950-1 and 62368-1
- AS/NZS 60950.1 and 62368.1

OPERATING CONDITIONS

- Temperature: -10 to +55°C (+14 to +131°F)
- Relative humidity: 5% to 95%, non-condensing
- Storage Temperature: -40 to +70°C (-40 to +158° F)

WEIGHT

- Repeater weight: 0.166 kg

UNIT BOX DIMENSIONS (W X H X D)/WEIGHT

- Repeater box dimensions: 239 x 141 x 44 (mm)
- Repeater box weight: 0.354 kg (with product, accessory, and documents)

MASTER CARTON QUANTITY

- 10

COUNTRY OF ORIGIN

- China

WARRANTY

- 1-year limited warranty

¹Most software-enabled features and capabilities must be supported by the server. Please contact your IP PBX/softswitch vendor or service provider for a list of supported features.

²Safety sheets are only included in EU units.

LEARN MORE

For more information on Poly Rove Family, visit poly.com/rove